



With special design and compound for only use of trailer or semi-trailer.

All these tyres in these catalogue cannot be used for lorries truck and buses.

## ***TYRE PRODUCT MANUAL***

This version is applied for BACH HO PCS., LTD; VIETNAM only



**YX111**



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
12R22.5	18PR	17.0	300	1085	9.00	3550/3250	152/149	L	930
11R22.5	18PR	14.5	272	1042	8.25	3250/3000	149/146	L	930

*\*This product cannot be used for lorries truck and buses.*



**YX858**



Suitable for only trailer or semi-trailer on mid-short distance transportation of paved road and mixed road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
12.00R20	20PR	18.5	306	1121	8.50	4000/3650	156/153	K	900

*\*This product cannot be used for lorries truck and buses.*



## YX608



Suitable for only trailer or semi-trailer on mid-short distance transportation of paved road and mixed road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
11R22.5	16PR	16.0	274	1050	8.25	3000/2725	146/143	M	830
12R22.5	18PR	18.0	296	1086	9.00	3550/3250	152/149	L	930
11R22.5	18PR	16.0	274	1050	8.25	3250/3000	149/146	M	830
315/80R22.5	20PR	16.0	312	1076	9.00	4625/4125	161/157	L	900
10.00R20	18PR	17.5	270	1048	7.50	3250/3000	149/146	K	930
11.00R20	18PR	16.5	288	1083	8.00	3550/3250	152/149	K	930
12.00R20	20PR	16.5	308	1118	8.50	4000/3650	156/153	K	900

*\*This product cannot be used for lorries truck and buses.*



## YX616



Suitable for only trailer or semi-trailer on mid-short distance transportation of paved road and mixed road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
11R22.5	16PR	15.0	279	1054	8.25	3000/2725	146/143	M	930
12R22.5	18PR	15.5	304	1078	9.00	3550/3250	152/149	K	930
315/80R22.5	20PR	15.0	306	1070	9.00	4125/3750	157/154	K	900
10.00R20	18PR	16.0	270	1046	7.50	3250/3000	149/146	K	930
11.00R20	18PR	17.0	288	1083	8.00	3550/3250	152/149	K	930
12.00R20	20PR	17.5	310	1119	8.50	4000/3650	156/153	K	900

*\*This product cannot be used for lorries truck and buses.*



**YX333**



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
12R22.5	18PR	18.0	300	1085	9.00	3550/3250	152/149	L	930

*\*This product cannot be used for lorries truck and buses.*



**YX668**



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
385/65R22.5	20PR	16.5	390	1070	11.75	4500	160	K	900
11R22.5	18PR	17.0	279	1054	8.25	3250/3000	149/146	L	930
12R22.5	18PR	18.0	296	1083	9.00	3550/3250	152/149	L	930
11.00R20	18PR	16.5	288	1083	8.00	3550/3250	152/149	K	930

*\*This product cannot be used for lorries truck and buses.*



联系电话:+86 15863067270

邮箱:superpan@yuexintyre.com

总部地址:厦门市海沧区鳌冠社区西片31-4号之四

青岛办事处:青岛市崂山区泉岭路8号中商国际大厦20层2005户

Mobile: +86 15863067270

Email: superpan@yuexintyre.com

HQ Add.: No. 31-4 quad, Western Part, Haicang District, Xiamen, China.

Qingdao Office: Room 2005, Floor 20th, Zhongshang International Mansion,  
Laoshan District, Qingdao, China.